

INTELLO X

Brand: ProClima

Product Code: 1AR00417

Weight: 19.84lb

Dimensions: 61.00in x 7.00in x 7.00in



Price: \$398.90

Short Description

Smart Vapor Control, and dense-pack reinforcement! Great for Commercial Use.

Description

INTELLO X is a robust exterior grade vapor variable air barrier. It offers the highest level of protection for insulated assemblies against moisture induced damages in enclosures - even for challenging constructions such as vapor closed flat roofs or highly insulated walls. It can act as a temporary WRB/roof and is ideal for commercial construction (metal studs, high rises, prefab panels) and for roof renovations from the exterior. It can be applied on the interior or, when temporarily exposed, applied on the exterior of buildings.

Advantages:

- Can be a temporary WRB or roof underlayment
- Permeability: VAPOR VARIABLE from 0.13 to over 13 perm - best in class (factor 100)
- Protective fleeces on both sides of smart retarder protect it from damages and UV exposure, and allow for durable tape bonds on both faces of the membrane
- Suitable for all types of insulation (fiberglass, mineral wool, cotton, sheepswool, woodfiber etc)
- Pro Clima Intelligent Airtight system (TESCON VANA tape, ROFLEX gaskets)

etc) allows for fast, reliable installation

- 10 year comprehensive [Pro Clima warranty](#)

Properties:

- Material: polyethylene copolymer protected by robust PP covers
- Waterproof, resists water column of 8'2" (2.5m)
- UV/weather Resistance: 2 months of exposure
- With recommended installation details can be used as dense pack insulation netting
- Class A material per ASTM E84 test (0 FS, 105 SDI)
- Hydrosave value of 1.6 perms, protects enclosure from construction humidity

Available roll sizes:

807 sq. ft. – 59"x164" (regular roll)